

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Graeme C. McKinnon
Filed : Herewith
For : GUIDEWIRE ANTENNA
Docket No.: S13.12-0106

JCS42 U.S. PTO
09/804430

TRANSMITTAL LETTER

"Express Mail" mailing label number: EL636049086US
Date of Deposit: August 10, 2000

The following paper(s) and/or fee(s) are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" addressed to BOX PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231:


1. Cut-up copy of original patent and new claims comprising the following pages:
 - 1 Cover Page
 - 8 Specification and claims
 - 8 New claims
2. Assent of Assignee to Reissue, Offer to Surrender and Power of Attorney
3. Request for Transfer of Original Drawings (Duplicate)
4. Order for Title Report (duplicate)
5. Our check in the amount of \$25.00 for Title Report
6. Patent Recordation Form Cover Sheet
7. Our check in the amount of \$40.00 for Recordation
8. Unexecuted Declaration of Graeme C. McKinnon

Under 37 CFR § 1.136(a)(3), applicant(s) hereby authorize(s) for any future reply, the incorporation of any required petition for extension of time for the appropriate length of time and authorize the charging of fees under § 1.17 to deposit account 23-1123.

Respectfully submitted,

WESTMAN, CHAMPLIN & KELLY, P.A.

By:


Joseph R. Kelly, Reg. No. 34,847
Suite 1600 - International Centre
900 Second Avenue South
Minneapolis, Minnesota 55402-3319
Phone: (612) 334-3222
Fax: (612) 334-3312

JRK:slg

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application for

Reissue of:

Patent of : GRAEME C. MCKINNON

Patent No. : 5,792,055

Appl. No. : 752,431

Filed : November 19, 1996

For : GUIDEWIRE ANTENNA

Docket No.: S13.12-0106

Group Art:

Examiner:

Brian L. Casler

ASSENT OF ASSIGNEE TO REISSUE, OFFER TO SURRENDER AND
POWER OF ATTORNEY

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Schneider (Europe) A.G., whose name has been changed to Schneider (Europe) GmbH, owner of the entire right, title and interest, by assignment, in the United States Letters Patent No. 5,792,055, granted on August 11, 1998, hereby assents to the above referenced application for reissue and hereby offers to surrender said Letters Patent.

Schneider (Europe) GmbH, hereby revokes all former Powers of Attorney and appoints the following attorneys and/or agents: Nickolas E. Westman, Reg. No. 20,147; Judson K. Champlin, Reg. No. 34,797; Joseph R. Kelly, Reg. No. 34,847; Steven M. Koehler, Reg. No. 36,188; David D. Brush, Reg. No. 34,557; John D. Veldhuis-Kroeze, Reg. No. 38,354; Deirdre Megley Kvale, Reg. No. 35,612; Theodore M. Magee, Reg. No. 39,758; Peter S. Dardi, Reg. No. 39,650; Christopher R. Christenson, Reg. No. 42,413; John A. Wiberg, Reg. No. 44,401; and Brian D. Kaul, Reg. No. 41,885; and Todd P. Messal, Reg. No. P-42,883; Albert Kau, Reg. No. 40,672; Luke R. Dohmen, Reg. No. 36,783 with full power of substitution and

revocation to prosecute said reissue application, to make alteration and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith.

Pursuant to 37 C.F.R. §3.73(b), Schneider (Europe) A.G., whose name has been changed to Schneider (Europe) GmbH, a corporation certifies that it is the assignee of the entire right, title and interest of the patent application identified above by virtue of an assignment from the inventor of the patent application identified above. The assignment was recorded at Reel 7313, Frame 0671.

Please direct all communication to Joseph R. Kelly, International Centre - Suite 1600, 900 Second Avenue South, Minneapolis, Minnesota 55402. Please direct all telephone calls to Joseph R. Kelly at telephone number (612) 334-3222.

SCHNEIDER (EUROPE) GmbH,

Date: _____

By: _____

Luke R. Dohmen

Its: Chief Patent Counsel
Cardiology

**LIMITED AUTHORIZATION TO ACT ON BEHALF OF ASSIGNEE
REGARDING CERTAIN PATENT MATTERS
EFFECTIVE THROUGH: December 31, 2000**

I, Janet M. Kelly, as Vice President and Corporate Controller of Boston Scientific Corporation, the controlling corporation of:

AMS Medinvent S.A.; Boston Scientific BV; Boston Scientific Corporation Northwest Technology Center, Inc.; Boston Scientific Ireland Limited; Boston Scientific Japan KK; Boston Scientific Limited; Boston Scientific Scimed, Inc.; Boston Scientific Technology, Inc.; BSC Technology, Inc.; CardioGene Therapeutics, Inc.; Cardiovascular Imaging Systems, Inc.; Cardiovascular Innovations Canada, Inc.; Corvita Canada, Inc.; Corvita Corporation; Corvita Europe S.A.; E.P. Technologies, Inc.; Laboratoires Corvita S.A.R.L.; Meadox Medicals, Inc.; Meadox Technology, Inc.; NAMIC Eireann Limited; NAMIC International, Inc.; Nilo Holding, S.A.; Schneider (Europe) GmbH; Schneider (USA), Inc.; Schneider Belgium NV; Schneider Holland BV; Schneider Ireland BV; Schneider Puerto Rico; Schneider/NAMIC; Scimed Life Systems, Inc.; Scimed Technology, Inc.; Symbiosis Corporation; and Target Therapeutics, Inc.;

and as Director, Treasurer, and Controller of Boston Scientific Limited;

hereby authorize the following registered patent attorneys/agents (1) to act on behalf of any of the corporations identified above, including Boston Scientific Corporation, with regard to any matters before the United States Patent and Trademark Office, any foreign patent offices, and any international patent entities, (2) to execute power of attorney documents on behalf of any of the corporations identified above, including Boston Scientific Corporation, to appoint and/or establish any attorneys, agents, and/or law firms to act on behalf of any of the corporations identified above, including Boston Scientific Corporation, in any foreign or international patent applications filed with any foreign and/or international patent offices, and (3) to execute assignment and ownership documents on behalf of any of the corporations identified above, including Boston Scientific Corporation, with regard to any matters before the United States Patent and Trademark Office, any foreign patent offices, and any international patent offices:

Scott T. Bluni	Reg. No. 40,916
David L. Cavanaugh	Reg. No. 36,476
Luke R. Dohmen	Reg. No. 36,783
Peter J. Gafner	Reg. No. 36,517
Albert K. Kau	Reg. No. 40,672
Todd P. Messal	Reg. No. 42,883
Robert M. Rauker	Reg. No. 40,782
William J. Shaw	Reg. No. 43,111

Janet M. Kelly
Janet M. Kelly, Vice President and Corporate Controller

12/2/00
Date

COMMONWEALTH OF MASSACHUSETTS)

COUNTY OF MIDDLESEX)

ss.

On this 21st day of June, 2000 before me personally appeared Janet M. Kelly to me known and known to me to be the person described in and who executed the foregoing instrument, and she duly acknowledged to me that she executed the same for the uses and purposes set forth herein.

Nona E. Hurd
Notary Public

**NONA E. HURD
NOTARY PUBLIC**

My Commission Expires Oct. 4, 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In the application of

GRAEME C. McKINNON.

Serial No. (not assigned)

Attention: **OIPE**

Filed **August 10, 2000**

Director - Thomas L. Koontz

For: GUIDEWIRE ANTENNA

for Reissue of Patent 5,792,055, Issued August 11, 1998

**REQUEST TO LOCATE AND URGENTLY PROCESS PTO-LOST
REISSUE APPLICATION FILED AUGUST 10, 2000**

Hon. Commissioner of Patents and Trademarks
Washington D.C. 20231

Sir:

On **August 10, 2000**, an application for Reissue of Patent 5,792,055 was filed by Express Mail in the PTO. The same was a "Missing Parts" application, lacking the inventor's signature and filing fee. Applicant's attorney received a PTO-dated postcard confirming the filing date of August 10, 2000. A copy of the postcard is attached, along with a copy of Express Mail Receipt EL636049086US showing the like Express mailing date of August 10, 2000.

No filing receipt, Missing Parts letter, or any other communication whatever has been received from the PTO in this case. It would appear that the PTO has misplaced the entire application.

Applicant's associate attorney has examined the PTO file of the parent original patent 5,792,055 in the chance that the new application may have been misplaced therein, but the patent file shows no indication of the reissue application.

Further, applicant's attorney has spent substantial time with Mr. Sean Hill of OIPE in an effort to locate this case in the PTO database. Diverse searches by inventor, parent patent number, docket number, and Express Mail number have all failed to show a PTO computer record of this case.

The PTO is accordingly requested to locate the lost application and immediately process the same under the filing date of August 10, 2000 as a usual reissue application for examination. Should the PTO be unable to locate the lost papers, applicant's attorney provides herewith a complete copy of the application as filed August 10, 2000, which the PTO may use in creating the application file for examination.

The attached copy of the Transmittal Letter identifies the copies of the papers submitted herewith which comprise the application.


The undersigned associate attorney certifies that the attached papers are true copies of the original reissue application as filed on August 10, 2000.

The PTO is invited to contact the undersigned local associate or the principal attorney should such be of assistance to the PTO.

Prompt action is respectfully requested in view of the passage of time since filing the application.

Respectfully submitted,

GRAEME C. McKINNON



by Warren N. Low

Reg. No. 18,849

Associate Attorney

P.O. Box 2184, Arlington, VA 22202

703-979-4870

Joseph R. Kelly, Esq. ·
Westman, Champlin & Kelly
612-334-3222
March 5, 2001

00733-04743333

GUIDEWIRE ANTENNA

CONTINUING DATA

This application is a continuation of application Ser. No. 08/311,700, filed 23 Sep., 1994, now abandoned.

BACKGROUND OF THE INVENTION

This invention relates to a medical appliance for use in magnetic resonance imaging procedures performed on a body, comprising an antenna detecting magnetic resonance response signals, the antenna intended to be inserted into the body for interacting with a magnetic resonance procedure for calculating the position of the medical appliance in the body.

Tracking of catheters and other devices positioned within a body may be achieved by means of a magnetic resonance imaging system in order to avoid using X-rays and the risk of accumulated X-ray dose to the patient and long term exposure to the attending medical staff.

Typically, such a magnetic resonance imaging system may be comprised of magnet means, pulsed magnetic field gradient generating means, a transmitter for electromagnetic waves in radio-frequency, a radio-frequency receiver, a processor, and a controller. The device to be tracked has attached to its end a small coil of electrically conductive wire. The patient is placed into the magnet means and the device is inserted into the patient. The magnetic resonance imaging system generates electromagnetic waves in radio-frequency and magnetic field gradient pulses that are transmitted into the patient and that induce a resonant response signal from selected nuclear spins within the patient. This response signal induces current in the coil of electrically conductive wire attached to the device. The coil thus detects the nuclear spins in the vicinity of the coil. The radio-frequency receiver receives this detected response signal and processes it and then stores it with the controller. This is repeated in three orthogonal directions. The gradients cause the frequency of the detected signal to be directly proportional to the position of the radio-frequency coil along each applied gradient.

The position of the radio-frequency coil inside the patient may therefore be calculated by processing the data using Fourier transformations so that a positional picture of the coil is achieved. Since however the coil only reacts, literally not a positional picture of the coil but in fact a positional picture of the position of the response signals inside the patient is achieved. Since this positional picture contains no information yet on the region surrounding the immediate vicinity of the coil, this positional picture can be superposed with a magnetic resonance image of the region of interest. In this case the picture of the region may have been taken and stored at the same occasion as the positional picture or at any earlier occasion.

Radio-frequency antennas in the form of a coil couple inductively to the electromagnetic field and they allow obtaining a substantially spatially uniform magnetic field which results in a relatively uniform image intensity over a wide region. The problem is however that coil configurations are bulky (the received signal is determined by the loop diameter) and cannot be implemented for use in narrow vessels, whereby their use for the placement of medical appliances such as catheters may be critical.

Furthermore, the spot image which is provided for by the coil antenna does not allow knowing or even evaluating the orientation of the device; as a result, the magnetic resonance

[illegible]

However, this is achieved within the environment of a bulky configuration which cannot be advanced through narrow vessels and which cannot be steered by reference to the magnetic resonance imaging system.

European Patent Application published under N 0385367 shows an insertable prostate pick-up probe devised for being a nuclear magnetic resonance receiving device capable of imaging spectra from the human prostate and surrounding tissue; this probe may also be used as the transmit coil for radio-frequency excitation. This probe is intended to be used with an interface network providing the tuning, impedance matching, and decoupling functions, and including a connection to a magnetic resonance imaging scanner.

3

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
0	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100

[illegible][illegible][illegible][illegible][illegible][illegible]

1 Variants may be envisaged.

For instance, the outer conductor and insulator, 15-16 resp. 150-160, need not be removed from a portion of the distal end 17 resp. 170. Similarly, the outer conductor and insulator may be removed a far greater length from the distal end 17 resp. 170, and it is also possible to have them removed to the proximal end of the guidewire, outside of the patient.

Subject to the precautions or requirements inherent to patient protection, it would be also possible to have the guidewire comprised of a naked conductor 13 or 130, while the insulator 14 or 140 and outer conductor 15, 150 and insulator 16, 160 would be installed towards the proximal end of the guidewire, outside of the patient.

Similarly, the coaxial configuration shown is not compulsory, being possible to have the open wire length antenna as a naked or insulated wire with appropriate polarities arranged for connection thereof to the antenna input of the control station.

FIG. 4 shows one such possibility, in which the open wire length antenna is made of two twisted conducting strands 18 and 19 insulated from one another by appropriate coatings 20 and 21.

FIG. 5 also shows one such possibility, in which the open wire length antenna is made of two conducting strands 22 and 23 parallel to one another and separated by insulator coatings 24 and 25.

As for the previous embodiments, the strands 18 and 19, respectively 22 and 23, may have the same length or unlike lengths.

In both the embodiments of FIG. 4 and FIG. 5, the channels 30 which are left open along the insulated strands may be used for further investigation purposes when the open wire length antenna is placed in the lumen of a catheter, for example for pressure readings.

I claim:

1. A medical appliance comprising an elongated signal-receiving antenna for detecting and providing magnetic resonance response signals, the antenna adapted to be inserted into the body during magnetic resonance imaging procedures and for providing the response signals used for calculating a position of the medical appliance in the body, wherein the antenna comprises an open wire length including first and second conductor means having proximal ends adapted and arranged for interconnection to a receiver to couple the detected resonance response signals to the receiver, spaced-apart distal ends, and at least a first insulator means for physically separating and electrically insulating adjacent portions of the first and second conductor means, the distal ends of the first and second conductor means and the at least first insulator means adapted and arranged for exposure to a field of electromagnetic energy during a magnetic resonance procedure to couple electromagnetic energy from the field into the antenna and detect and provide the magnetic resonance response signals to the proximal ends of the conductor means.

2. A medical appliance according to claim 1, wherein the open wire length antenna is formed of a coaxial cable including the first and second conductors in a coaxial arrangement.

3. A medical appliance according to claim 1, wherein the open wire length antenna is formed of a cable having the first conductor enclosed in the first insulator, the first insulator surrounded by the second conductor and the second conductor encased in a second insulator, and wherein said first conductor and second conductor have the same length.

4. A medical appliance according to claim 1, wherein the open wire length antenna is formed of a cable having the first conductor enclosed in the first insulator, the first insulator surrounded by the second conductor, and the second conductor encased in a second insulator, and wherein said first conductor and second conductor have unlike lengths.

5. A medical appliance according to claim 1, wherein the open wire length antenna is made of the first conductor, the first insulator includes a first insulating coating applied on said first conductor, the second conductor includes a conducting coating surrounding said first insulating coating, and the antenna further includes a second insulating coating applied on said conducting coating, and wherein said first conductor and conducting coating have the same length.

6. A medical appliance according to claim 1, wherein the open wire length antenna is made of the first conductor, the first insulator includes a first insulating coating applied on said first conductor, the second conductor includes a conducting coating surrounding said first insulating coating, and the antenna further includes a second insulating coating applied on said conducting coating, and wherein said first conductor and conducting coating have unlike lengths.

7. A medical appliance according to claim 1, wherein the first and second conductors of the open wire length antenna include conducting strands insulated from one another.

8. A medical appliance according to claim 7, wherein the first and second conductor means are parallel to one another.

9. A medical appliance according to claim 7, wherein the first and second conductor means are twisted.

10. A medical appliance according to claim 7, wherein the first and second conductor means have the same length.

11. A medical appliance according to claim 7, wherein the first and second conductor means have unlike lengths.

12. A medical appliance according to claim 1, wherein the open wire length antenna forms at least a part of a guidewire for vascular procedures.

13. A medical appliance antenna system for use in connection with magnetic resonance imaging procedures, including:

a medical appliance comprising an elongated signal-receiving antenna for detecting and providing magnetic resonance response signals, the antenna adapted to be inserted into the body during magnetic resonance imaging procedures and for providing the response signals used for calculating a position of the medical appliance in the body, wherein the antenna includes an open wire length including first and second conductors having proximal ends adapted and arranged for interconnection to a receiver to couple the detected response signals to the receiver, spaced-apart distal ends, and at least a first insulator for physically separating and electrically insulating adjacent portions of the first and second conductors, the distal ends of the first and second conductors and the at least first insulator adapted and arranged for exposure to a field of electromagnetic energy during a magnetic resonance procedure to couple the electromagnetic energy from the field to the antenna and detect and provide the magnetic resonance response signals to the proximal ends of the conductors; and

a receiver electrically connected to the antenna for receiving the magnetic resonance response signals and pro-

21. A medical appliance according to claim 20, wherein the open wire length antenna is formed of a coaxial cable including the first and second conductors in a coaxial arrangement.

22. A medical appliance according to claim 20, wherein the open wire length antenna is formed of a cable having the first conductor enclosed in the first insulator, the first insulator surrounded by the second conductor and the second conductor encased in a second insulator, and wherein said first conductor and second conductor have the same length.

23. A medical appliance according to claim 20, wherein the open wire length antenna is formed of a cable having the first conductor enclosed in the first insulator, the first insulator surrounded by the second conductor, and the second conductor encased in a second insulator, and wherein said first conductor and second conductor have unlike lengths.

24. A medical appliance according to claim 20, wherein the open wire length antenna is made of the first conductor, the first insulator includes a first insulating coating applied on said first conductor, the second conductor includes a conducting coating surrounding said first insulating coating, and the antenna further includes a second insulating coating applied on said conducting coating, and wherein said first conductor and conducting coating have the same length.

25. A medical appliance according to claim 20, wherein the open wire length antenna is made of the first conductor, the first insulator includes a first insulating coating applied on said first conductor, the second conductor includes a conducting coating surrounding said first insulating coating, and the antenna further includes a second insulating coating applied on said conducting coating, and wherein said first conductor and conducting coating have unlike lengths.

26. A medical appliance according to claim 20, wherein the first and second conductors of the open wire length antenna include conducting strands insulated from one another.

27. A medical appliance according to claim 20 and further including a receiver electrically connected to the antenna for receiving the magnetic resonance response signals and providing information representative of the position and orientation of the medical appliance.

* * * * *

28. A medical apparatus for imaging a wall of a body cavity in a patient by interacting with a magnetic resonance imaging (MRI) system which generates a magnetic field gradient and electromagnetic (EM) radiation and transmits the gradient and EM radiation into the patient and receives a response signal indicative of a resonant response from the patient, the apparatus comprising:
an antenna including an open conductor length configured to be inserted into the cavity and provide the response signal, based on the resonant response from a region of the patient closely proximate the antenna, to the MRI system;
and
a controller coupled to the antenna and configured to receive the response signal to obtain an image of the cavity wall proximate the antenna.

29. The medical apparatus of claim 28 wherein the controller is configured to calculate antenna location by calculating an image of the antenna, antenna position, and antenna orientation.

30. The medical apparatus of claim 28 wherein the controller is configured to repeatedly measure, reconstruct and store the image to obtain an increased resolution image of the cavity wall.

31. The medical apparatus of claim 28 wherein the antenna is configured to be capacitively coupled to an EM field generated by the EM radiation.

32. The medical apparatus of claim 28 wherein the cavity is defined by vasculature in the patient and wherein the antenna is configured for insertion into and passage through the vasculature.

33. The medical apparatus of claim 32 wherein the antenna forms at least a portion of a guidewire configured for insertion into the vasculature for use in positioning of a catheter.

34. The medical apparatus of claim 28 wherein the MRI system includes a response signal receiver and processor and a control station, and wherein the controller is implemented as a part of the control station or processor.

35. The medical apparatus of claim 28 wherein the antenna includes a first elongate conductor having a portion thereof forming the open conductor length, and a second elongate conductor, the first and second elongate conductors extending to a proximal end of the antenna.

36. The medical apparatus of claim 35 wherein the first and second elongate conductors are coaxially arranged along at least a portion of a length thereof.

37. The medical apparatus of claim 35 wherein the first and second elongate conductors are separated by an insulative layer.

38. The medical apparatus of claim 35 wherein the first and second elongate conductors are formed as a twisted pair.

39. The medical apparatus of claim 35 wherein the first and second elongate conductors are generally linear and generally parallel to one another.

40. A method of generating an image of a wall of a body cavity in a patient, the method comprising:

inserting an antenna including an open conductor length into the cavity;

generating a magnetic field gradient and

electromagnetic (EM) radiation and transmitting the gradient and EM radiation into the patient;

transmitting a response signal, based on a detected resonant response from a region of the patient closely proximate the antenna, to a magnetic resonance imaging (MRI) processor;

receiving the response signal at the MRI processor; and

obtaining an image of the cavity wall proximate the antenna based on the response signal.

41. The method of claim 40 wherein obtaining an image comprises:

repeatedly calculating antenna location.

42. The method of claim 41 wherein calculating antenna location comprises:

calculating an image of the antenna.

43. The method of claim 41 wherein calculating antenna location comprises:

calculating antenna position.

44. The method of claim 41 wherein calculating antenna location comprises:

calculating antenna orientation.

45. The method of claim 40 wherein obtaining an image comprises:

repeatedly measuring, reconstructing and storing the image to obtain an increased resolution image of the cavity wall.

46. The method of claim 40 wherein transmitting a response signal comprises:

capacitively coupling the antenna to an EM field generated by the EM radiation to detect the resonant response.

47. The method of claim 40 wherein the cavity is defined by vasculature in the patient and wherein inserting an antenna into the cavity comprises:

inserting the antenna into the vasculature; and passing the antenna through the vasculature to a site to be imaged.

48. The method of claim 47 wherein the antenna is configured as a guidewire and further comprising:

positioning a catheter in the vasculature through use of the guidewire.

49. A method of generating an image of a blood vessel wall of a blood vessel in a patient, the method comprising:

inserting an antenna into the blood vessel;
passing the antenna through the blood vessel to a site
to be imaged;
generating a magnetic field gradient and
electromagnetic (EM) radiation and transmitting
the gradient and EM radiation into the patient;
transmitting a response signal, based on a detected
resonant response from a region of the patient
closely proximate the antenna, to a magnetic
resonance imaging (MRI) processor;
receiving the response signal at the MRI processor;
and
obtaining an image of the blood vessel wall proximate
the antenna based on the response signal.

50. A medical apparatus for imaging a blood vessel wall of
a blood vessel in a patient by interacting with a magnetic
resonance imaging (MRI) system which generates a magnetic
field gradient and electromagnetic (EM) radiation and
transmits the gradient and EM radiation into the patient
and receives a response signal indicative of a resonant
response from the patient, the apparatus comprising:
an antenna configured to be inserted into the blood
vessel and passed along the blood vessel to a
site to be imaged and to provide the response
signal, based on the resonant response from a
region of the patient closely proximate the
antenna, to the MRI system; and
a controller coupled to the antenna and configured to
receive the response signal and repeatedly
calculate antenna location to obtain an image of
the blood vessel wall proximate the antenna.

51. The medical apparatus of claim 50 wherein the antenna comprises an open conductor length.

52. The medical apparatus of claim 51 wherein the antenna includes a first elongate conductor having a portion thereof forming the open conductor length, and a second elongate conductor, the first and second elongate conductors extending to a proximal end of the antenna.

53. The medical apparatus of claim 50 wherein the antenna is configured to be capacitively coupled to an EM field generated by the EM radiation.

54. A medical apparatus for imaging a body cavity wall of a body cavity in a patient by interacting with a magnetic resonance imaging (MRI) system which generates a magnetic field gradient and electromagnetic (EM) radiation and transmits the gradient and EM radiation into the patient and receives a response signal indicative of a resonant response from the patient, the apparatus comprising:

an MRI antenna configured to be inserted into the body cavity and passed along the body cavity to a site to be imaged and to provide the response signal, based on the resonant response from a region of the patient closely proximate the antenna, to the MRI system.

55. The medical apparatus of claim 54 wherein the body cavity is a blood vessel and further comprising:

a controller coupled to the antenna and configured to
receive the response signal and repeatedly

calculate antenna location to obtain an image of
the blood vessel wall proximate the antenna.

56. A method of generating an image of a wall of a body
cavity in a patient, the method comprising:

inserting a magnetic resonance imaging (MRI) antenna
into the body cavity;

passing the MRI antenna through the body cavity to a
site to be imaged; and

obtaining an MRI image of the body cavity wall
proximate the antenna.

57. The method of claim 56 wherein obtaining an image
comprises:

generating a magnetic field gradient and
electromagnetic (EM) radiation and transmitting
the gradient and EM radiation into the patient;
transmitting a response signal, based on a detected
resonant response from a region of the patient
closely proximate the antenna, to an MRI
processor;

receiving the response signal at the MRI processor;
and

calculating antenna location based on the response
signal.

58. The method of claim 57 wherein calculating antenna
location comprises:

repeatedly calculating antenna location.

59. The method of claim 56 wherein obtaining an MRI image
comprises:

calculating an image of the antenna.

60. The method of claim 56 wherein obtaining an MRI image comprises:

calculating antenna position.

61. The method of claim 56 wherein obtaining an MRI image comprises:

calculating antenna orientation.

62. The method of claim 56 wherein the body cavity is a blood vessel and obtaining an MRI image comprises:

repeatedly measuring, reconstructing and storing the image to obtain an increased resolution image of the blood vessel wall.

63. The method of claim 57 wherein transmitting a response signal comprises:

capacitively coupling the antenna to an EM field generated by the EM radiation to detect the resonant response.

64. The method of claim 56 wherein the body cavity is defined by vasculature and the antenna is configured as a guidewire and further comprising:

positioning a catheter in the vasculature through use of the guidewire.

[illegible]

S13.12-0106






1. I am the first and sole inventor of the subject matter claimed in U.S. Patent No. 5,792,055 to McKinnon, issued August 11, 1998 and entitled GUIDEWIRE ANTENNA, filed on November 19, 1996 as a continuation of application serial number 08/311,700, filed September 23, 1994 (now abandoned), for which I solicit a reissue pursuant to 35 U.S.C. §252.

3. I believe my original patent to be wholly or partly inoperative because I claimed less than I had a right to claim in the original patent. I believe my claims in the original patent do not reflect the full breadth of my invention for the reasons set forth below.

5. All errors corrected in this reissue application up to the date of filing this declaration arose without deceptive intent.

Inventor: _____ Date: _____
(Signature)

Inventor: Graeme C. McKinnon



OIPE
Group Art Unit:
Examiner:

JKC:1rb